

GASPROMNEFT SN-500

Base export oils



DESIGNATION AND DESCRIPTION

Mineral base oils are intended for the most commercial lubricants production. They are produced from the vacuum distillates and residual components using the traditional refining methods (selective treatment, dewaxing, further deresination for the residual component).

ADVANTAGES

- high oxidation stability
- good susceptibility to the additives
- low sulfur content
- excellent viscosity-temperature characteristics



TYPICAL CHARACTERISTICS

	SN-500
Kinematic viscosity at 100 $^{\circ}\text{C}$, mm $^2/\text{s}$	11,1
Viscosity index	90
Flash point COC, $^{\circ}\text{C}$	244
Pour point, $^{\circ}\text{C}$	-15
Total Acid number, mg KOH/g	0,0058
Ash, %	0,005
Sulfur content, %	0,40
Evaporation Loss, %	6,21
Density, at 15 $^{\circ}\text{C}$, g/sm 3	0,889
Color	3

Manufacturer: "Gazpromneft-Lubricants", Ltd., Russian Federation, 117647, Moscow, Profsoyuznaya Street, 125A; 644040, Omsk, Gubkina av., 1. according to STO 84035624-003-2008

The above stated figures are typical for those products, obtained with the normal production tolerances and do not constitute the specification data. The information is for reference only and can be changed or modified without prior notification. August 23, 2016.