# **Technical Data Sheet**

### **Divinol Turbo 15W-40**

### **Product description**

Divinol Turbo 15W-40 is a SHPD-multigrade oil, which can be used for the whole motor vehicle fleet. Outstanding cleaning and dirt carrying properties (dispersant and detergent properties) enable longer oil change intervals (according to the manufacturer). The oil simplifies stock keeping in mixed vehicle fleets because of universal, non-seasonal usability for diesel and otto engines.

#### Specification

API SJ/CF-4; ACEA A3-02/B3-98/E2-96

#### Manufacturer performance

VW 501.01/505.00; Allison C-4; Caterpillar TO-2; Volvo VDS; MAN 271; MB-Approval 228.1/ 229.1; MTU Type 1; Valtra E

Divinol recommendation: ACEA A3-02/B3-98/E2-96

#### Characteristics

SAE Grade:	15W40
Ash / Sulfate DIN 51575:	1 %
Viscosity/40°C / DIN 51 562:	90 mm²/s
Viscosity/100°C / DIN 51 562:	13 mm²/s
Viscosity index / DIN ISO 2909:	145
Density/15°C / DIN 51 757:	0,870 g/cm³
Pour point / DIN ISO 3016:	-28°C
Flash point (Cleveland) / DIN ISO 2592:	220°C
TBN:	8 mgKOH/g

#### 49681

06/2016-49681-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.





ZG Division: Divinol Lubricants & Release Agents Zeller+Gmelin GmbH & Co. KG Schlossstr. 20 - 73054 Eislingen/Fils Tel. +49 7161 802-0 - Fax +49 7161 802-230 www.zeller-gmelin.de - dst@zeller-gmelin.de



# **Technical Data Sheet**

## **Divinol Turbo 15W-40**

#### Application

For supercharged, fast running diesel / gasoline engines in utility vehicles (busses, transporters, heavy goods vehicles for building work) which are in permanent use with dirt, dust, heat and cold influence.

49681

06/2016-49681-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2/2



ZG Division: Divinol Lubricants & Release Agents Zeller+Gmelin GmbH & Co. KG Schlossstr. 20 - 73054 Eislingen/Fils Tel. +49 7161 802-0 - Fax +49 7161 802-230 www.zeller-gmelin.de - dst@zeller-gmelin.de

