

Technical Data Sheet

Divinol ATF Spezial R

Product description

Divinol ATF Spezial R is a power transmission oil for automatic transmissions and fulfils the following requirements:

- Superior oxidation stability
- Very good anti wear characteristics
- Premium cold flow properties
- Broad temperature range deployment
- Not aggressive to any sort of seal

Specification

GM Dexron III G; GM Dexron II D; GM Dexron TASA; Ford Mercon 2004

Manufacturer approval

Voith H55.6335.XX

Manufacturer performance

Allison C-4; Caterpillar TO-2; MAN 339 V1/Z1; MB-Aproval 236.6; Renk; Sperry Vickers; Sundstrand; Volvo 97340; ZF TE-ML 02F, 03D, 04D, 05L, 09, 11B, 14A

Characteristics

Appearance:	red
Viscosity/40°C / DIN 51 562:	35 mm ² /s
Viscosity/100°C / DIN 51 562:	7.1 mm ² /s
Viscosity index / DIN ISO 2909:	170
Density/15°C / DIN 51 757:	870 kg/m ³
51830	

02/2016-51830-9

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol ATF Spezial R

Pour point / DIN ISO 3016: < -40 °C

Flash point (Cleveland) / DIN ISO 2592: 200 °C

Application

Divinol ATF Spezial R is suitable as transmission oil in automatic transmissions of cars, trucks, busses and special vehicles. Also possible for hydrodynamic converters, hydraulics and servo-steerings in accordance to manufacturers' specifications.

51830

02/2016-51830-9

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2